



Zep Commercial Sales & Service
 1310 Seaboard Industrial Blvd.
 Atlanta, GA 30318
 1-888-805-HELP (4357)
 www.zepcommercial.com

Safety Data Sheet

Section 1. Chemical Product and Company Identification

Product name Industrial Purple Cleaner and Degreaser Concentrate
Product code ZU0856
Date of issue 7/16/13 **Supersedes** 12/07/12
 Not available.

Emergency Telephone Numbers

For MSDS Information:
 Compliance Services 404-352-1680

For Medical Emergency
 (877) 541-2016 Toll Free - All Calls Recorded

For Transportation Emergency
 CHEMTREC: (800) 424-9300 - All Calls Recorded
 In the District of Columbia (202) 483-7616


Prepared By
 Compliance Services
 1420 Seaboard Industrial Blvd.
 Atlanta, GA 30318

Section 2. Hazards Identification

Emergency overview

*Hazard Determination System (HDS): Health, Flammability, Reactivity

DANGER !



CAUSES EYE AND SKIN BURNS. HARMFUL IF INHALED OR ABSORBED THROUGH SKIN. HARMFUL OR FATAL IF SWALLOWED.

NOTE: MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

Acute Effects **Routes of Entry** Dermal contact. Eye contact. Inhalation.

Eyes Causes eye burns. Eye exposure may cause severe and permanent eye injury (blindness).

Skin Causes skin burns. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening or, occasionally, blistering.

Inhalation Avoid breathing vapors, spray or mists. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath. Over-exposure by inhalation may cause respiratory irritation. Can cause central nervous system (CNS) depression.

Ingestion Harmful if swallowed. May cause burns to mouth, throat and stomach.

Chronic effects Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray or mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

Carcinogenicity No known significant effects or critical hazards.

Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

Section 3. Composition/Information on Ingredients

<u>Name of Hazardous Ingredients</u>	<u>CAS number</u>	<u>% by Weight</u>
sodium hydroxide	1310-73-2	1 - 10
Butoxyethanol; Butyl Cellosolve; 2-butoxyethanol	111-76-2	1 - 10
Fatty acids, tall-oil	61790-12-3	1 - 5
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts	68439-57-6	1 - 5
Alkyl(C9-11) alcohol, ethoxylated	68439-46-3	1 - 5

Section 4. First Aid Measures

Eye Contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
Skin Contact	Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention immediately.
Inhalation	Move exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.
Ingestion	Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

National Fire Protection Association (U.S.A.)



Flash Point	Closed cup: >88°C (>190.4°F)
Flammable Limits	Not applicable
Flammability	Non-combustible.
Fire hazard	In a fire or if heated, a pressure increase will occur and the container may burst. May emit toxic fumes under fire conditions.
Fire-Fighting Procedures	Use an extinguishing agent suitable for the surrounding fire. Do not release runoff from fire to drains or watercourses.

Section 6. Accidental Release Measures

Spill Clean up	Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
-----------------------	---

Section 7. Handling and Storage

Handling	Put on appropriate personal protective equipment (see section 8). Avoid contact with eyes, skin and clothing. Do not breathe vapor or mist. Use with adequate ventilation. Do not ingest. Do not reuse container. Wash thoroughly after handling. Observe label precautions.
Storage	Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Store between the following temperatures: 40°F - 120°F (4.4°C - 49°C). Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection**Product name**

sodium hydroxide

Exposure limits

ACGIH TLV (United States, 2/2010).

C: 2 mg/m³

OSHA PEL 1989 (United States, 3/1989).

CEIL: 2 mg/m³

NIOSH REL (United States, 6/2009).

CEIL: 2 mg/m³

OSHA PEL (United States, 6/2010).

TWA: 2 mg/m³ 8 hour(s).

OSHA PEL 1989 (United States, 3/1989). Absorbed through skin.

TWA: 25 ppm 8 hour(s).

TWA: 120 mg/m³ 8 hour(s).

NIOSH REL (United States, 6/2009). Absorbed through skin.

TWA: 5 ppm 10 hour(s).

TWA: 24 mg/m³ 10 hour(s).

ACGIH TLV (United States, 2/2010).

TWA: 20 ppm 8 hour(s).

OSHA PEL (United States, 6/2010). Absorbed through skin.

TWA: 50 ppm 8 hour(s).

TWA: 240 mg/m³ 8 hour(s).

Butoxyethanol; Butyl Cellosolve; 2-butoxyethanol

Personal Protective Equipment (PPE)

- Eyes** Splash goggles. Face shield.
- Body** Wear appropriate protective clothing to prevent skin contact.
Recommended: Neoprene gloves. Nitrile gloves. Rubber gloves.
Synthetic apron. Chemical resistant boots.
- Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

**Section 9. Physical and Chemical Properties**

Physical State	Liquid.	Color	Clear. Purple.
pH	13.0 - 14.0	Odor	Mild. Ethereal.
Boiling Point	98.9°C (210°F)	Vapor Pressure	Not determined.
Specific Gravity	1.055	Vapor Density	>1 [Air = 1]
Solubility	Easily soluble in the following materials: cold water and hot water.	Evaporation Rate	1 (Water = 1)
		VOC (Consumer)	3.4 % (w/w) 0.299 lbs/gal (35.9 g/l)

Section 10. Stability and Reactivity

- Stability and Reactivity** The product is stable.
- Incompatibility** Reactive or incompatible with the following materials: oxidizing materials, metals and acids.
- Hazardous Polymerization** Will not occur.
- Hazardous Decomposition Products** carbon oxides (CO, CO₂)

Section 11. Toxicological Information**Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Sodium Hydroxide	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	500 mg/kg	-
2-butoxyethanol	LC50 Inhalation Gas.	Rat	450 ppm	4 hours
	LC50 Inhalation Vapor	Guinea pig	>633 ppm	1 hours
	LD50 Dermal	Guinea pig	>2000 mg/kg	-
	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
Benzenesulfonic acid, C10-16-alkyl derivs.	LD50 Oral	Rat	250 mg/kg	-
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Oral	Rat	775 mg/kg	-
Alkyl(C9-11) alcohol, ethoxylated	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1378 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

Section 12. Ecological Information

- Environmental Effects** Not available.

Aquatic Ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
sodium hydroxide	-	Acute EC50 40.38 mg/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - Neonate - <24 hours	48 hours
	-	Acute LC50 125000 ug/ L Fresh water	Fish - Western mosquitofish - Gambusia affinis - Adult	96 hours
Butoxyethanol; Butyl Cellosolve; 2-butoxyethanol	-	Acute EC50 >1000 mg/ L Fresh water	Daphnia - Water flea - Daphnia magna - <24 hours	48 hours
	-	Acute LC50 800000 ug/ L Marine water	Crustaceans - Common shrimp, sand shrimp - Crangon crangon	48 hours
	-	Acute LC50 1250000 ug/L Marine water	Fish - Inland silverside - Menidia beryllina - 40 to 100 mm	96 hours
Sulfonic acids, C14-16-alkane hydroxy and C14-16-alkene, sodium salts	-	Acute EC50 4.53 mg/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - Neonate - <24 hours	48 hours
	-	Acute EC50 5.36 mg/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia -	48 hours

-	Acute EC50 2686 ug/L Fresh water	Neonate - <24 hours Daphnia - Water flea - 48 hours Daphnia magna - Neonate - <24 hours
-	Acute LC50 8500 ug/L Fresh water	Fish - Fathead minnow - 96 hours Pimephales promelas




Section 13. Disposal Considerations

Waste Information

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

Waste Stream Code: D002
Classification: - [Hazardous waste]
Origin: - [RCRA waste.]

Section 14. Transport Information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	UN3266	Corrosive liquid, Basic, Inorganic, NOS (sodium hydroxide)	8	II	
TDG Classification	UN3266	Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide)	8	II	
IMDG Class	UN3266	Corrosive liquid, basic, inorganic, n.o.s. (sodium hydroxide)	8	II	

NOTE: DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG* : Packing group

Section 15. Regulatory Information

U.S. Federal Regulations

SARA 313 toxic chemical notification and release reporting:

Product name

Butoxyethanol; Butyl Cellosolve; 2-butoxyethanol

Clean Water Act (CWA) 311: sodium hydroxide;

Clean Air Act (CAA) 112 regulated toxic substances: No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

State Regulations

California Prop 65

None of the components are listed.

Canada

WHMIS (Canada)

Class D-1A: Material causing immediate and serious toxic effects (Very toxic).

Class E: Corrosive material

Section 16. Other Information

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.